California Environmental Protection Agency		EXECUTIVE ORDER A-006-1246-1
	GENERAL MOTORS CORPORATION	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mi	IL LIFE ies)	INTER! IN- COMP (*=N/A or A/E=ex intermed	MEDIATE -USE -LIANCE -full in-use; :h. / evap. liate in-use)	FUEL TYPE			
2005 5GN	5GMXT06.0199	MDV: 5751-8500 Pounds ALVW	USEPA Bin 8a (opt)	EXH / ORVR	EVAP	EXH	EVAP	Compressed			
Station and a contract of the			Counted as ARB SULEV	120K	*	* *		Natural Gas			
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE FAMILY (EVAF)			DISPLACEMENT (L)					
1	2WU-TWC,21	WC, 2HO2S(2), SFI, OBD(F)	5GMXE	5GMXE0000801							
*		•	5GMXE								
•		*	1	•			(	\$			
•		*	•	•							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1246 dated July 9, 2004.

Executed at El Monte, California on this 2157 day of September 2004.

a ne he

Allen Lyons, Chief Mobile Source Operations Division

California Environmental Protection Agency AIR RESOURCES BOARD

9

**GENERAL MOTORS CORPORATION** 

EXECUTIVE ORDER A-006-1246-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on casoline te

NMOG FLEET NMOG AVERAGE [g/mi] CH4		NMOG CH4	@ RAF=* RAF = *	NMOG or	CH4=met HCHO=fc	hane; NMOG ormaldehyde;	=non-CH4 c PM=particu	organic gas; late matter; l	NMHC=nc RAF=react	on-CH4 hy tivity adjus	drocarbon	; CO=carbon or; 2/3 D (g/te	monoxide; l st]=2/3 day	NOx=oxides ( diumai+	of nitrogen;	
CERI	T STD	NMOG	NMHC	NMHC STD	hot-soak; mi=mile;	RL [g/mi]=rui K=1000 miles	nning loss; ( s; F≖degree	ORVR [g/gall s Fahrenheit	ion dispen	upplement	board refue tai federal t	ling vapor re est procedur	covery; g≃g e	ram; mg=mil	igram	
*		[a/mi]	[a/mi]	[g/mi]		2 [g/mi]	NO	x [g/mi]	НС	CHO [mg	/mi]	PM [g	/ml]	Hwy N	Ox [g/mi]	
y					CERI	STD	CERT	STD		RT	STD	CERT	STD	CERT	STD	
	(C SUK	0.017		0.125	1.0	3.4	0.10	0.14	1.(	0	15.	•	*	0.13	0.19	
	QUL	0.017	•	0.156	1.0	4.2	0.10	0.20	1.0	0	18.	•		0.13	0.27	
	@ 50°F & 4K	*	•	*	*	*	•	*	*		•	*	*	•	+	
C	CO [g/mi]		a kanala manakana kanala ka		NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NOx JS06]	)x CO [g/r )6] [US06		NMH [g/mi]	C+NOx [SC03]	CO	CO [g/mi] [SC03]	
		an an an an Anna an An An an Anna an A		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
CERT	*	SFTP	@ * miles	•	*	*	*	•	*	*		*	•	*	•	
STD	•	SFTP	@ * miles	*	*	*	*	•	•	+	*	*	+	+	•	
Evaporative Family (gran CERT		urnal + Ho is/test) @ L	nal + Hot Soak 2-Days Diurr test) @ UL (grams/t		urnal + Hot Soak s/test) @ UL		Running Loss (grams/mile) @ UL		Re	On-Board Refueling Vapor Recovery (grams/gallon) @ UL						
		CERT	S	TD CERT S		TD	CERT		STD	D CERT		STD				
5GMXE0000801		•	*		•		*			•	*		+			
5GMXE0000802		2	*			•		•	•							
			•		•	*		•			*					
					······										-	

\* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=wam-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttie body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

## 2005 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERN IN- COMP (*=N/A or A/E=ext Intermedi EXH	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		OBD II
CHEVROLET	C2500 HD SILVERADO 2WD	5GMXE0000801	1	6	•	+	*	Full
CHEVROLET	K2500 HD SILVERADO 4WD	5GMXE0000801	1	6	•	*	*	Full
GMC	C2500 HD SIERRA 2WD	5GMXE0000801	1	6		•	*	Fuil
GMC	K2500 HD SIERRA 4WD	5GMXE0000801	1	6	•	*	*	Full
CHEVROLET	C2500 HD SILVERADO 2WD	5GMXE0000802	1	6	•	•	+	Full
CHEVROLET	K2500 HD SILVERADO 4WD	5GMXE0000802	1	6	*	•	•	Full
GMC	C2500 HD SIERRA 2WD	5GMXE0000802	1	6	*	•	*	Full
GMC	K2500 HD SIERRA 4WD	5GMXE0000802	1	6	*	*	*	Full