

#### KIA MOTORS CORPORATION

Executive Order: A-314-0331

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	IFOR	MATION					
	ODEL YEAR TEST GROUP			VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2020	) LK	MXV01.6CC5		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
-	USEFUL	LIFE (miles)	VEH	IICLE EMIS	ATE	GORY	INTERIM / IN	RMEDIATE IN-USE STD					
EXH/ORVR EVAP				FTP SFTI			TP	FTP		SFTP			
15	150000 150000			LEV3	ULEV70	LEV 3 COMPO		MPOSITE	PM		PM		
SPE	CIAL FE	ATURES & EX	(HAU STE		ON CONTRO	DL		OBD S	TATUS		ENGINE DISPLACEMENT (L)		
1	DFI,	WR-HO2S, HO	WU-TWC, T	WC, TC, C	AC		FULL	FULL SOME MODELS					
*			*			Р	ARTIAL	SOME MODELS	11	1.6			
*			* .			D 200 CONTRACTOR	PARTIAL WITH *		1				
		E	VAP	ORATIVE &	REFUELING	G (EVA	P/OR	VR) FAMIL	/ INFORMATIO	N			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
I	LKMXR01	30CCE	L	LEV 2			E	rc ·	*				
				E	EMISSION C	REDIT	INFO	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY  NMOG CREDIT FOR NON-I ZERO-EVAP						ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEE	TAVE	RAGE	INFORMA	TION				
NMOG RAF	CH4 RAF RAFIO  HCHO/NMHC RATIO  RATIO  RATIO  NMOG+NOX FL PC+LDT (0-375 (g/mi)				(0-3750					NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	(	0.065		T	0.074 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### KIA MOTORS CORPORATION

Executive Order: A-314-0331

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of May 2019.

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



LKMXR0130CCE

TIER 2

UNLEADED

0.02 0.20

KIA MOTORS CORPORATION Executive Order: A-314-0331

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

# **ATTACHMENT**

								· · · · · ·	, i i i v i								
	EXH								_	_	RDS ANI					.S	
		E	XHAU								LEVELS						
	Fu	mor adju OR\				NOx: ox factor; C/gallo	rides of n 2DHS/3D n dispens	itrogen; H )HS [g HC sed]: on-b	ICHO: :/test]: oard re	forma 2/3 da efuelin	: hydrocai ldehyde; F ays diurnal g vapor re est proced	PM: particu +hot-soak; covery; g:	late i ; RL   gram	matter; R [g HC/mi] i; mg: mil	AF: reac  : running ligram; m	tivity i loss:	
	: ##				NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCH(mg/m				PM (g/mi)		
	inger"			CE	RT	STD	CER	T ST	D	CERT	STD	CER	Г	STD	CERT	STD	
FTP@5	0K	*			*	*	*	*		*	*	*		*	*	*	
FTP@l	JL TI	ASOLINE- IER3 E10 0.0		042	0.070	0.6	1.	7	*	*	*		4	0.001	0.003		
50°F @4K GAS			INE-	1 0	033	0.140	0.5	1.	7	*	*	*		16	(port april)	1 301 124 A	
The state of the s					FUEL TYPE					NMOG+NOx (g/mi)			-		ni)		
					FUEL TYPE					C	ERT	STD		CERT		STD	
HWFE.	T @ 50H	<				*				*	*	*		and the second second	agos <del>er de</del> kor e trabit		
HWFE	HWFET @ UL				GASOLINE-TIER3 E10					0	0.027 0.070			C. A. D. F.			
20°F	20°F @ 50K COLD CO E10 R				10 REG	GULAR GASOLINE (TIER3)			AND CHARAMA TOTAL			ao	0.8		10.0		
				SFT	P EXHA	USTE	MISSION	STAND	ARDS	AND	CERTIFIC	ATION LE	VEL	S			
- No.					US06						SC03			COMPOSITE			
	FUEL	JEL TYPE		l.	NMOG+NOx (g/mi)		CO (g/mi)	CO PM (g/mi) (mg/r		NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NOx (g/mi)		CO (g/mi	PM ) (mg/mi)	
@ 4K	4K *		CERT				*				*	*					
				STD	*		*				*	*					
	GASOLIN		SOLINE-		*		*		1.	-	*	*		0.044	0.7		
@ UL		R3 E10 STI		STD	*		*		6 		* *		0.083		4.2	*	
				BIN		A.40								0.070			
		<u>V</u>	WHO	LE VEH	ICLE E						DS AND C		OITA	N LEVEL	.S		
	EVAPORATIVE		-  -					g/test) @ UL			dS (g/test)			RL (g/mi) @ UL			
FAMILY					CERT		STD	STD FEL		RT	STD	FEL		CERT		STD	
TKMXR0130CCE I		OLINE PHASE	102010		0.50	*	* 0.4		0.65	*	* 0.0		0.05				
C	ORVR /	FUE	LON	NLY / CA	NISTE	R BLEI	ED EVAP	ORATIVE	EMIS	SSION	STANDA	RDS AND	CE	RTIFICAT	TION LE	<b>VELS</b>	
EVAP	ORATIV	/E	0	RVR (g/					30	HS R	JEL ONLY EVAP & CAN			TEST	BLEED (	CANISTER	
FA	MILY	′		L T)(DE				- · · · · · · -		g/test) @ UL		(g/test) @				test) @ 4K	
				L TYPE	CERT	STI	'	<del> </del>		RT	STD	CERT	+	STD	CERT	STD	
		10			I	1	1		1				1	- 1		1	



### KIA MOTORS CORPORATION

Executive Order: A-314-0331

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	
KIA	FORTE	PC	1.6	AM7,M6	LKMXR0130CCE	1	<b>F</b>	
KIA	FORTE (W/SCC)	PC	1.6	AM7	LKMXR0130CCE	1	P	
KIA	FORTE 5	PC	1.6	AM7	LKMXR0130CCE	1	F	
KIA	FORTE 5 (W/SCC)	PC	1.6	AM7	LKMXR0130CCE	1	P	