

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMA	TION					
MODE		EST GROUP	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2020	L	KMXV01.6L2T		PLUG-IN HYBRID ELECTRIC VEHICLE				GASOLINE				
	USEFU	L LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGOR	Y	INTERIM / INT	EDIATE IN-USE STD			
EXH	/ORVR	EVAP		SFTP FTP				SFTP				
15	0000	150000	LEV3	SULEV30	LEV	3 COMPO	OSITE	PM		PM		
SPE	CIAL F	EATURES & EXI	HAUST EMISSI	ON CONTRO	DL		OBD S	STATUS	EN	IGINE DISPLACEMENT		
1	DFI, W	R-HO2S, HO2S	, WU-TWC, TW	C, EGR, E	GRC	FU	LL	ALL MODELS				
*			*		PAR	TIAL	*	1.6				
*			*		PARTIA		*					
		EV	APORATIVE &	REFUELING	G (EVA	P/ORVR)	FAMIL	Y INFORMATION				
EVA	P / OR\	R FAMILY	EVAPORATIVE	STD CATE	GORY			ISSION STD E CLASS	SI	PECIAL FEATURES		
LKMKR0110L2G L				3 OPTION2			PC			HCT		
				EMISSION C	REDIT	INFORM	ATION					
GROUP AV			AVE. CRED				PZEV ZERO-		OG CREDIT FOR OPTIONAL DOR FOR WORI			
		ZEV										
	ALL I	MODELS	N			N		N		N		
			NMOG	AND FLEE	TAVE	RAGE INI	FORMA	TION				
MOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NO PC+LDT					1			
*	*	1.10	*	(	0.065	0.074			*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

L FEATL

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_day of November 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division



KIA MOTORS CORPORATION Executive Order: A-314-0346 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

## ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

GASOLINE-

TIER3 E10

0.06

0.20

LKMXR0110L2G

			1.1									1.	
	NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		M mi)		
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL		DLINE- R3 E10	0.018	0.030	0.4	1.0	*	*	*	4	0.001	0.003	
50°F @4K	GASOLINE- TIER3 E10		1 0 019 1		0.2	1.0	*	*	*	8			
S.CARLES	Sec.				-		NN	OG+NO	x (g/mi)		CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CEF	RT	STD	
HWFET @ 50K			*						*	- ANTERNA	William Ro	ar arrest	
HWFET @ UL		L GASOLINE-TIER3 E10						05	0.030				
20°F @ 50K		COLD	CO E10 RE	EGULAR G	ASOLINE	(TIER3)			enter an	1.	5	10.0	
			SETP EXH	AUSTEM	ISSION ST		SAND CE	RTIFICA	TION LEVE	LS	4. C		

### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

						U	S06				SC03			CO	MPOSITE	
	FUEL TY	PE			OG+NOx (g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)		OG+NO> (g/mi)	c CO (g/mi)	PM (mg/mi
@ 4K	*		CERT		*		*				*	*	ed Kall			
			STD		*		*			*		*	122.4	in street	1.1996	
	GASOLINE- TIER3 E10		I STD I		*		*	1			*	*		0.016	0.3	*
@ UL					STD *		*			6		+		*	0.083	
			BIN				S. 983	in Rolling	al and	No.A		See Lower		0.030		
		WH	OLE VE	HICL	E EVAPO	DRAT	IVE E	MISSION	STAN	DAR	DS AND C	ERTIFIC	ATIO	N LEVEL	S	
						WH	OLE V	EHICLE	EVAP	ORAT	IVE TEST	ING				
EVAPORATIVE FAMILY					S (g/t	(g/test) @ UL			2DHS (g/test) @ UL				RL (g/mi) @ UL			
					CERT	ST	rD	FEL	CE	RT	STD	FEL CE		CER	CERT STI	
LKMXR0110L2G			ASOLIN LEV3 E	_	0.199	0.3	300	*	0.1	51	0.300	*		0.00		0.05
(	DRVR / FUE	EL C	DNLY/C	CANIS	STER BL	EED	EVAPO	ORATIVE	EMIS	SION	STANDA	RDS AND	DCE	RTIFICA	TION LEV	ELS
									FL	JEL C	NLY EVA	P & CAN	ISTE	R BLEED	)	
	ORATIVE	•	ORVR (	g/gall	lon) @ Ul	- [	FUE				G TEST @ UL	2DHS RIG T (g/test) @				
		FU	EL TYP	EC	ERT S	TD				RT	STD	CERT	T	STD	CERT	STD

\*

\*

\*

\*

\*

\*

CALIFORNIA	KIA MOT
AIR RESOURCES BOARD	CORPOR
AIR RESOURCES BOARD	

KIA MOTORS

Executive Order: A-314-0346 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIV	E LEAK DIAMETER STANDA	RD AND CERTIFICATION L	EVEL (INCHES)
		CERT	STD
LKMXR0110L2G	LKMXR0110L2G-DEP	0.00	0.02

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection: DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission: CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	KIA	NIRO PLUG-IN HYBRID	PC	1.6	AM6	LKMXR0110L2G	1	F

## ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV	
NUMBER	PHEVITPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE
1	TZEV	38.4	39.5	*	34.8	34.4	0.70