

 CALIFORNIA AIR RESOURCES BOARD	MITSUBISHI MOTORS CORPORATION	Executive Order: A-086-0391 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4
--	----------------------------------	---

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION									
MODEL YEAR	TEST GROUP		VEHICLE CLASS(ES)		FUEL CATEGORY		FUEL TYPE		
2020	LMTXT02.0H3M		LDT2		PLUG-IN HYBRID ELECTRIC VEHICLE		GASOLINE		
USEFUL LIFE (miles)			VEHICLE EMISSION CATEGORY			INTERIM / INTERMEDIATE IN-USE STD			
EXH/ORVR		EVAP	FTP		SFTP	FTP		SFTP	
150000		150000	LEV3 SULEV30		LEV 3 COMPOSITE	PM		PM	
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS					OBD STATUS		ENGINE DISPLACEMENT (L)		
1	EGR, WR-HO2S, WU-TWC, HO2S, TWC, SFI				FULL	*	2.0		
*	*				PARTIAL	ALL MODELS			
*	*				PARTIAL WITH FINES	*			
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION									
EVAP / ORVR FAMILY		EVAPORATIVE STD CATEGORY			EVAP EMISSION STD VEHICLE CLASS		SPECIAL FEATURES		
LMTXR0148A2L		LEV 3 OPTION2 WITH FEL			LDT2		*		
EMISSION CREDIT INFORMATION									
ALLOWANCE FOR TEST GROUP		NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY		NMOG CREDIT FOR NON-PZEV ZERO-EVAP		NMOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS	
TZEV									
ALL MODELS		N		N		N		N	
NMOG AND FLEET AVERAGE INFORMATION									
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)		NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10	0.002	0.065		0.074		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



MITSUBISHI MOTORS
CORPORATION

Executive Order: A-086-0391
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 3rd day of July 2019.

Kim Pryor
for Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

	FUEL TYPE	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP									
		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE-LEV3 E10	0.0254	0.030	0.70	1.0	*	*	0.0	4	0.0000	0.003
50°F @4K	GASOLINE-LEV3 E10	0.0392	0.060	0.71	1.0	*	*	0.1	8		

	FUEL TYPE	NMOG+NOx (g/mi)		CO (g/mi)	
		CERT	STD	CERT	STD
HWFET @ 50K	*	*	*		
HWFET @ UL	GASOLINE-LEV3 E10	0.0082	0.030		
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			1.39	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	FUEL TYPE		US06			SC03		COMPOSITE		
			NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
@ UL	GASOLINE-LEV3 E10	CERT	*	*	1.8	*	*	0.014	1.40	*
		STD	*	*	6	*	*	0.083	4.2	*
		BIN						0.050		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE	WHOLE VEHICLE EVAPORATIVE TESTING						RL (g/mi) @ UL	
		3DHS (g/test) @ UL			2DHS (g/test) @ UL				
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LMTXR0148A2L	GASOLINE- LEV3 E10	0.1546	0.400	0.300	0.1268	0.400	0.300	0.004	0.05

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL ONLY EVAP & CANISTER BLEED						
				FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K	
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
LMTXR0148A2L	GASOLINE- TIER3 E10	0.018	0.20	*	*	*	*	*	*	*



CALIFORNIA
AIR RESOURCES BOARD

MITSUBISHI MOTORS
CORPORATION

Executive Order: A-086-0391
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)

EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
LMTXR0148A2L	LMTXR0148A2L-A2L	*	0.02

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium-duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZE: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	MITSUBISHI MOTORS	OUTLANDER PHEV	LDT2	2.0	A1	LMTXR0148A2L	1	P

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL NUMBER	PHEV TYPE	UDDS AER (MILES)	UDDS EAER (MILES)	US06 AER (MILES)	HIGHWAY (MILES)		ZEV ALLOWANCE
					AER	EAER	
1	TZEV	32.7	30.0	*	31.2	30.9	0.60