

Executive Order: A-008-0521

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION															
MODE		EST GROUP	P VEHICLE CLASS				FUEL CATEGORY					FUEL TYPE			
2021	МВ	MXJ02.0H30	PC					1	PLUG-IN HYBRID ELECTRIC VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHI					ICLE EMIS	CLE EMISSION CATEGORY INTERIM / IN					T	FERMEDIATE IN-USE STD			
EXH	EXH/ORVR EVAP FTP			TP SFTP				FTP			SFTP				
15	0000	150000		LEV3	SULEV30	LEV	3	COMPOSIT	TE	*		PM			
SPE	CIAL FE	ATURES & EXI	IAUST		ON CONTRO	OL		ОВ	BD ST	TATUS		ENGINE DISPLACEMENT			
1	WU-TW	C, TWC, WR-H	02S,	HO2S, D	FI, TC, C	AC		FULL		*					
*			*					PARTIAL	-	*	2.0				
*			*				P	ARTIAL WI	ΊΤΗ	ALL MODELS		1			
		EV	APOR	RATIVE &	REFUELING	G (EVA	P/	ORVR) FAI	MILY	INFORMATIO	V				
EVAP / ORVR FAMILY EVAPORATIVE STD CATE					GORY	′	EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES				
M	BMXR01	40G3H	LEV	V 3 OPTI	ON2 WITH	FEL			P	PC			*		
				1	EMISSION C	REDI	T IN	FORMATI	ON						
7			/E. CRED			-PZ	REDIT FOR ZEV ZERO-	DOB			FOR OPTIONAL EXH. STD FOR WORK TRUCKS				
		EV		N				N	+	N		-	N		
	ALL M	ODELS			ANDELEE	T A\/E	: D A		DAMA				24		
	NMOG AND FLEET AVERAGE INFORMATION														
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	1	O/NMHC ATIO	NMOG+NO PC+LDT			VW) L	W) LDT (3751 LVW-8500 MDV (10,001-14,			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*		0.058			0.065 *				*		
O 4b	- A44l-		1 - 0.0 -	dala Fire	nanativa F	a mails	En	aine Dienl	local	mont Emission	2 (	Cont	rol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-008-0521

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

# BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

## BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2021 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 37 day of April 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



Executive Order: A-008-0521 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# **ATTACHMENT**

	EXH											D CERT				/ELS	3
		EXH	AUST	EMISS	SION	STAND	ARDS A	ND CEF	RTIFIC	ATION	LEVELS	(FTP, HW	/FET	, 50°F, 2	20°F)		
	FUE	≣L TY	r   a   0	nonox adjustr DRVR	H4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon nonoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity djustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; RVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP												
					IOG+I (g/mi			CO (g/mi)			lOx /mi)	1	HCH mg/i			-	
				CER	Т	STD	CER	r st	D	CERT	STD	CER	Т	STD	CE	RT	STD
FTP@5		*		*		*	*	*		*	*	*		*	,	ŀ	*
FTP@l		R3 E		0.02	2 (	0.030	0.5	1.	0	*	*	*		4	0.0	002	0.003
50°F @	AMC	OLIN R3 E		0.01	8 (	0.060	0.3	1.	0	*	*	*		8			
					FU	EL TY	DE .			N	MOG+N	Ox (g/mi)			CO (	g/mi)	
							-			CE	RT	STD		CEF	RT		STD
HWFE.	T @ 50K		-			*					*	*					
HWFE	T@UL			GA	SOLIN	E-TIE	R3 E10			0.	0.011 0.030						
20°F	@ 50K	CC	LD CO	E10	REGU	JLAR G	ASOLIN	E (TIE	R3)					0.6		10.0	
			S	FTP E	EXHA			STAND	ARDS	AND C		ATION LE	VEL				
				-			US06 SC03						COMPOSITE				
	FUEL T	YPE		1	lOG+N (g/mi)		CO (g/mi)	1	/M J/mi)		G+NOx mi)	CO (g/mi)			1		PM (mg/mi)
@ 4K	*		CERT		*		*				*	*					
			STD		*		*				*	*					
			CERT	-	*		*		2	,	*	*	(	0.016	c	.7	*
@ UL	GASOLI TIER3		STD		*		*		6	,	*	*	(	0.077	4	1.2	*
			BIN														
		WH	OLE V	EHICL	E EV								ATIO	N LEVE	LS		
	ORATIVE		UEL T	VDE	2		HOLE V		EVAP		/E TEST (g/test)			RL (g/mi) @ UL			
FA	MILY	'	OLL I	11-6	CEF		STD	FEL	CE		STD	FEL		CEF	?T		STD
MBMXR	.0140G3F	2 1	ASOLI		0.1	_	.300	0.300	0.1	_	0.300	0.30					0.05
-	RVR / FI				STER	BLEE	D EVAPO	DRATIVI	EEMIS	SION S	TANDA	RDS AND	CEF	RTIFICA	TION	LEVE	LS
		T															
	ORATIVE		ORVR	(g/gal	lon) @	UL	FUEI	TYPE		HS RIG g/test) (		2DHS I (g/tes		non-CH4 HC; CO: car e matter; RAF: reactivi L [g HC/mi]: running lo am; mg: milligram; mi: r upplemental FTP  CHO PM g/mi) (g/m  STD CERT  * * 4 0.002  8 CO (g/mi)  CERT S  COMPOSITE  MOG+NOX CO (g/mi) (g/mi)  0.016 0.7  0.077 4.2  0.050  ON LEVELS  RL (g/mi) @ L  CERT S  0.00 0  ERTIFICATION LEVELE ER BLEED  STEST BLEED CAN			
		FU	EL TYI	PE C	ERT	STD			_	RT	STD	CERT	1		CER	T	STD
MBMXR	0140G3F		SOLINI ER3 E:		0.01	0.20		*		it	*	*		*	*		*



Executive Order: A-008-0521

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MBMXR0140G3H	MBMXR0140G3H-001	0.00	0.02							

t: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC: HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission: SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	BMW	330E	PC	2.0	SA8	MBMXR0140G3H	1	\$
2	BMW	330E XDRIVE	PC	2.0	SA8	MBMXR0140G3H	1	\$

## **ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION**

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHWAY (MILES)		ZEV	
NUMBER	PHEV TIPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE	
1	TZEV	26.69	29.25	*	30.82	30.95	0.59	
2	TZEV	26.69	29.25	*	30.82	30.95	0.59	